

COMPRESSOR DEFINITION

Designation	T 2155E
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	116BA23

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-22		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure R22		
4.1 Evaporating temperature range	-30°C to -10°C	(-22°F to 14°F)	
5 Motor type	CSCR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	21.7	[kgf/cm ²] (309 psig)	/ °C - °F
9.2 Peak (gauge)	24.2	[kgf/cm ²] (344 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/2+	[hp]
2 Displacement	17.39	[cm ³] (1.061 cu.in)
2.1 Bore [mm]	34.120	
2.2 Stroke [mm]	19.030	
3 Lubricant charge	550	[ml] (18.60 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO46	
4 Weight (with oil charge)	16.28	[kg] (35.89 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELECTRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Voltage Relay	
2.1 Starting device	3ARR3B10AB3	
3 Start capacitor	72-88(330)	[µF(VAC minimum)]
4 Run capacitor	15(450)	[µF(VAC minimum)]
5 Motor protection	3HM193-105	
6 Start winding resistance	9.15	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	4.10	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	18.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	2.10	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification		

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Fan		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
2048	516	600	484	2.19	11.18	4.23	1.07	1.24

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-30	(-22)	1604	404	470	366	1.77	8.73	4.38	1.10	1.28
-25	(-13)	2210	557	648	427	2.03	12.06	5.18	1.31	1.52
-20	(- 4)	2972	749	871	494	2.31	16.27	6.02	1.52	1.76
-15	(+ 5)	3890	980	1140	568	2.61	21.38	6.85	1.73	2.01
-10	(+14)	4964	1251	1455	650	2.94	27.40	7.64	1.92	2.24

TEST CONDITIONS: @220V50Hz			ASHRAE32 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-30	(-22)	1460	368	428	379	1.78	7.95	3.86	0.97	1.13
-25	(-13)	2021	509	592	443	2.05	11.03	4.56	1.15	1.34
-20	(- 4)	2731	688	800	515	2.37	14.95	5.30	1.33	1.55
-15	(+ 5)	3590	905	1052	596	2.72	19.73	6.02	1.52	1.77
-10	(+14)	4597	1158	1347	686	3.12	25.37	6.70	1.69	1.96

TEST CONDITIONS: @220V50Hz			ASHRAE32 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-30	(-22)	1322	333	387	391	1.78	7.19	3.38	0.85	0.99
-25	(-13)	1840	464	539	459	2.07	10.04	4.01	1.01	1.17
-20	(- 4)	2500	630	733	536	2.42	13.68	4.66	1.18	1.37
-15	(+ 5)	3301	832	967	623	2.83	18.14	5.30	1.34	1.55
-10	(+14)	4244	1069	1244	720	3.29	23.42	5.89	1.48	1.73

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	9.6 +0.07/+0.00	[mm]	(0.378" +0.003"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Vertical		
3.2 DISCHARGE	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Vertical		
3.3 PROCESS	9.6 +0.07/+0.00	[mm]	(0.378" +0.003"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Vertical		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		